



Item # 20013094, SPIRAFLEX VACUUM Hose 2 in x 100 ft, 737 psi, White

APPLICATION: Spiraflex® Vacuum hose is for dust collection and exhaust transmission where airborne pollutants, fumes and odors are a major problem.

CONSTRUCTION TUBE: White Pliovic® compound

REINFORCEMENT: Rigid white high-density Pliovic® helix

TEMPERATURE: 0 °F to 158 °F (-18 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Vacuum Transfer
Style	Vacuum Hose
Construction Tube	White Pliovic® compound
Reinforcement	Rigid white high-density Pliovic® helix
Color	WHITE
Min. Temperature	0 °F -18 °C
Max. Temperature	158 °F 70 °C
Max. Working Pressure	30.0 psi

	0.21 MPa
Brands	SPIRAFLEX® VACUUM
Order Code	586-403

Specifications

I.D.	2 in 50.80 mm
Nom. O.D.	2.350 in 59.70 mm
Length	100.000 ft
Bend Radius	6.000 in 140.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	0.450 lb/ft 0.67 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech